

## FEATURES & BENEFITS

- High strength galvanized steel hardware tested to 75,000 lbs. of tensile strength providing superior strength and corrosion resistance
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Swivel eyes prevent twisting and moderate strain on the tackle
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

## GENERAL SPECIFICATIONS

Diameter	52 ½" / 1344 mm
Wall Thickness	¼" / 6 mm
Height	62" / 1574 mm
Air Weight	295 lbs / 134 kg
Total Displacement	4079 lbs / 1850 L

## MATERIAL SPECIFICATIONS

### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

### COLOUR

Comes in standard yellow

### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

### GALVANIZED STEEL

Internal components are hot-dipped galvanized

## AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

