

### FEATURES & BENEFITS

- High strength galvanized steel hardware tested to 75,000 lbs. of tensile strength providing superior strength and corrosion resistance
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Swivel eyes prevent twisting and moderate strain on the tackle
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

### GENERAL SPECIFICATIONS

Diameter	1344 mm
Wall Thickness	6 mm
Height	2006 mm
Air Weight	163 kg
Total Displacement	2500 L

### MATERIAL SPECIFICATIONS

#### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

#### COLOUR

Comes in standard yellow

#### EPS FOAM

16 kg/m<sup>3</sup> density closed cell EPS foam used

#### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

#### GALVANIZED STEEL

Internal components are hot-dipped galvanized

### AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

