

FEATURES & BENEFITS

- Highest quality, UV stabilized with uniform wall thickness ensures a robust life expectancy to 15+ years
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Seamless one-piece construction provides a watertight product
- Impact resistant even at low temperatures means it's suitable for harsh applications in saltwater or freshwater bodies
- Free of internal voids prevents significant water ingress and produces superior structural integrity

GENERAL SPECIFICATIONS

Diameter	244 mm
Wall Thickness	6 mm
Height	1956 mm
Air Weight	33 kg
Displacement	84 L
Reserve Buoyance with min mooring mass	12 kg

MATERIAL SPECIFICATIONS

POLYETHYLENE

Virgin PE material used with a UV 15 inhibitor

COLOUR

Comes in standard white

EPS FOAM

16 kg/m³ density closed cell EPS foam used

STAINLESS STEEL

Bushing and inserts are made with a minimum rating of 18-8 stainless steel

CONCRETE

Bottoms of buoys have a 25 kg concrete ballast

AVAILABLE OPTIONS

- Radar reflector
- Lighted top
- Conical top
- Custom signage
- Custom colours
- IALA standard colours
- (Available options are subject to min. order quantity)

