

## FEATURES & BENEFITS

- Full length 6" diameter steel tube replacing the standard rod allows for versatility in mooring and easier visual inspection of the tackle
- Highest quality, UV stabilized, seamless one-piece construction with uniform wall thickness and galvanized internals ensure a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

## GENERAL SPECIFICATIONS

Diameter	52 ½" / 1.34 m
Wall Thickness	¼" / 6 mm
Height	62" / 1.57 m
Air Weight	368 lbs / 167 kg
Total Displacement	4079 lbs / 1850 L

## MATERIAL SPECIFICATIONS

### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

### COLOUR

Comes in standard yellow

### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

### GALVANIZED STEEL

Internal components are hot-dipped galvanized

## AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

