

## FEATURES & BENEFITS

- Full length 6" diameter steel tube replacing the standard rod allows for versatility in mooring and easier visual inspection of the tackle
- Highest quality, UV stabilized, seamless one-piece construction with uniform wall thickness and galvanized internals ensure a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

## GENERAL SPECIFICATIONS

|                    |                   |
|--------------------|-------------------|
| Diameter           | 52 1/2" / 1344 mm |
| Wall Thickness     | 3/8" / 9.5 mm     |
| Height             | 62" / 1574 mm     |
| Air Weight         | 368 lbs / 167 kg  |
| Total Displacement | 4079 lbs / 1850 L |

## MATERIAL SPECIFICATIONS

### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

### COLOUR

Comes in standard yellow

### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

### GALVANIZED STEEL

Internal components are hot-dipped galvanized

## AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

