

### FEATURES & BENEFITS

- Full length 6" diameter steel tube replacing the standard rod allows for versatility in mooring and easier visual inspection of the tackle
- Highest quality, UV stabilized, seamless one-piece construction with uniform wall thickness and galvanized internals ensure a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

### GENERAL SPECIFICATIONS

Diameter	52 ½" / 1334 mm
Wall Thickness	¼" / 6 mm
Height	79" / 2006 mm
Air Weight	457 lbs / 207 kg
Total Displacement	5512 lbs / 2500 L

### MATERIAL SPECIFICATIONS

#### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

#### COLOUR

Comes in standard yellow

#### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

#### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

#### GALVANIZED STEEL

Internal components are hot-dipped galvanized

### AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

