

## FEATURES & BENEFITS

- High strength galvanized steel hardware with a tested safe working load of 15,000 lbs providing superior strength and corrosion resistance
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Swivel eyes prevent twisting and moderate strain on the tackle
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material

## GENERAL SPECIFICATIONS

Diameter	52 ½" / 1344 mm
Wall Thickness	¼" / 6 mm
Height	42" / 1069 mm
Air Weight	185 lbs / 84 kg
Total Displacement	2646 lbs / 1200 L

## MATERIAL SPECIFICATIONS

### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

### COLOUR

Comes in standard yellow

### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

### STAINLESS STEEL


Inserts are made with a minimum rating of 18-8 stainless steel

### GALVANIZED STEEL


Internal components are hot-dipped galvanized

## AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours



Ø 508  
Load Plate  
Fastened With 5 Bolts  
Both Ends



Ø 1344

Locking Nut  
Welded In Place  
Both Ends

#8 Swivel Eye Nut  
Both Ends

Collar Built Into  
Load Plate

DETAIL A  
SCALE 1 : 15

