

### FEATURES & BENEFITS

- High strength galvanized steel hardware providing superior strength and corrosion resistance
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Free of internal voids prevents significant water ingress and produces superior structural integrity
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Impact resistant even at low temperatures means it's suitable for harsh applications in saltwater or freshwater bodies

### GENERAL SPECIFICATIONS

Diameter	18" / 468 mm
Wall Thickness	1/8" / 5 mm
Height	25" / 627 mm
Air Weight	11 lbs / 5 kg
Total Displacement	112 lbs / 51 L
Buoyancy @ Waterline	40 lbs / 18 kg

### MATERIAL SPECIFICATIONS

#### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

#### COLOUR

Comes in standard white with the top 1/3<sup>rd</sup> above water line orange

#### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

#### GALVANIZED STEEL

Internal components are hot-dipped galvanized

### AVAILABLE OPTIONS

- Reflective banding
- Custom colours
- Custom graphics
- (Available options are subject to min. order quantity)

