

## FEATURES & BENEFITS

- High strength galvanized steel hardware with a tested safe working load of 15,000 lbs / 6,804 kg providing superior strength and corrosion resistance
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Swivel eyes prevent twisting and moderate strain on the tackle
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material
- 3M™ Flexible Prismatic Reflective 4" wide yellow tape applied as standard

## GENERAL SPECIFICATIONS

Diameter	36" / 914 mm
Wall Thickness	1/4" / 6 mm
Overall Height	46" / 1171 mm
Air Weight	77 lbs / 35 kg
Net Buoyancy	1500 lbs / 680 kg

## MATERIAL SPECIFICATIONS

### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

### COLOUR

Comes in standard yellow

### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel

### GALVANIZED STEEL

Internal components are hot dip galvanized

## AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

